



1. MATERIAL:  
HOUSING: PA9T UL94V-0, COLOR: BLACK,  
CONTACTS: PHOSPHOR BRONZE T=0.10±0.01mm.
2. FINISH:  
0.020±0.3um [1u"] MIN. GOLD PLATED FOR CONTACT AREA  
1.27um [50u"] MIN. NICKEL FOR ALL
3. ELECTRICAL:  
CONTACT RESISTANCE: 20 mΩ .  
INSULATOR RESISTANCE: 1000 mΩ min  
CURRENT RATING: 2 A .  
DIELECTRIC WITHSTANDING VOLTAGE: AC 500V.
4. ENVIRONMENTAL:  
OPERATING TEMPERATURE: -25°C TO +85°C

B2	2013.11.6	Δ2 增加间距, 由4.00-4.25	CXW	DZ	APVD
B1	2009.8.14	Δ1	MD	DZ	APVD
B	2009.7.3	RELEASED	MD	DZ	APVD
ECON(DCN) NO.	REV.	DATE	DESCRIPTION	CHANGE	APVD

TOLERANCES UNLESS OTHERWISE SPECIFIED		<b>JS</b> HAOGUO(Zhongxiang) Limited Company
X	±0.30	
XX	±0.25	Customers Drawing
XXX	±0.10	REPTABLE ASSY 3POS 2MM PITCH
X.X	±0.25	Part No.
X.X	±0.25	SEE TABLE
X.X	±0.25	Drawing No.
X.X	±0.25	C-02-0004
X.X	±0.25	Scale
X.X	±0.25	1 : 1

NO	02-0004-02
YES	02-0004-01
<b>MALAR</b>	<b>PART NO.</b>

UNIT	mm	SIZE	A4
Sheet	1 of 1		
Third Angle Projection			