



RECOMMEND P.C.B. LAYOUT
PCB TOLERANCE:±0.05

- NOTE:
1. MATERIAL:
HOUSING: PA66+30%GF, UL 94V-0 COLOR: (SEE TABLE)
POSTS: BRASS
2. FINISH: GOLD/TIN FLASH OVER 50 μ m MIN. NICKEL PLATED.
3. ELECTRICAL:
POSTS RESISTANCE: 40 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING: 500V AC.
CURRENT RATING: 2.5A MAX.
VOLTAGE RATING: 500V AC/DC MAX.
4. ENVIRONMENTAL:
OPERATING TEMPERATURE: -40° TO +85°C.

Ab

1*4	--	11-0012-04	NATURAL	ALL PIN	-	12.50	7.50	BRIGHT TIN	
1*2	--	11-0012-03	NATURAL	ALL PIN	-	7.50	2.50	GOLD FLASH	
1*8	WD0612504HW018RD	11-0012-02	NATURAL	1.4 \pm 0.05	PIN	4	22.50	17.50	GOLD FLASH
1*2	WD0316002HW018RD	11-0012-01	NATURAL	-	-	7.50	2.50	GOLD FLASH	
POLES	OLD PRAT NO.	OLD PRAT NO.	COLOR	KINK PINS	LACK PINS	DIM A	DIM B	POSTS FINISH	

TOLERANCES UNLESS OTHERWISE SPECIFIED
X: ±0.30 X: ±2°
XX: ±0.25 X.X: ±1°
XXX: ±0.10

JS HAOGUO(Zhongxiang) Limited Company
Customers Drawing TITLE: 2.50 WAFER CONNECTOR

A1	2013.11.20	ADD PART NUMBER	CXW	DZ	DWN	CHUXINWEI	Part NO.	SEE TABLE	Scale	1:1
A	27Feb2010	NEW	Ben	JY	CHKD	CYONG-JIANG	Drawing No.	C-11-0012	Sheet	1 of 1
ECON(DCN) NO.	REV.	DATE	CHANGE	APVD	APVD	DAVID	UNIT	mm	SIZE	A4

Third Angle Projection